

 **KOYODYAMA**
TIRES



Better Balanced Tires

Powered by **ZERO WAVE™** Technology



GRANDTRACK AT25

EXCELLENT ALL-TERRAIN TRACTION


- Enhanced Dry & Wet Handling
- Effective Hydroplaning Resistance
- Superior Wear Resistance & Long Mileage
- Low-Noise & Comfortable Ride
- Balanced All-Season Adaptability



Adapts to paved and light off-road conditions for consistent grip across scenarios.



Continuous center ribs boost straight-line stability and cornering precision.



Optimized grooves evacuate water quickly to reduce hydroplaning risk and shorten wet braking distance.



Even contact pressure distribution prevents uneven wear for extended tread life.



Variable pitch pattern reduces road noise for a quieter, more comfortable urban commute.



GRANDTRACK AT25

Rim Diameter	Tire Size	Service Desc	PR	UTQG	Single Max Load (kg)	Single Max Load (lbs)	Dual Max Load (kg)	Dual Max Load (lbs)	Measuring Rim (in)	Overall Diameter (mm)	Section Width (mm)	Max Inflation Pressure (kPa)	Max Inflation Pressure (PSI)
16	265/70R16	112T	/	600 A B	1120	2469	/	/	8J	778	272	300	44
	275/70R16	114H	/	600 A B	1180	2601	/	/	8J	792	279	300	44
17	265/65R17	112T	/	600 A A	1120	2469	/	/	8J	776	272	300	44
	275/65R17	115T	/	600 A A	1215	2679	/	/	8J	790	279	300	44
	285/65R17	116H	/	600 A A	1250	2756	/	/	8 1/2J	802	292	300	44
	265/70R17	115T	/	600 A B	1215	2679	/	/	8J	804	272	300	44
	225/70R17C	108/106S	6PR	/	1000	2205	950	2095	6 1/2J	748	228	325	48
18	265/60R18	110H	/	600 A A	1060	2337	/	/	8J	775	272	300	44
	265/65R18	114H	/	600 A A	1180	2601	/	/	8J	801	272	300	44
	285/60R18	116V	/	600 A A	1250	2756	/	/	8 1/2J	799	292	300	44

GRANDTRACK AT30

ENHANCED OFF-ROAD TRACTION

- Puncture-Resistant & Durable Construction
- Stable Handling on Wet & Dry Roads
- Durable Wear & Long Mileage Performance



Deepened and widened tread blocks improve grip and passability on unpaved roads.



Reinforced carcass and tread blocks resist punctures and cuts from gravel and debris.



Optimized groove design balances water evacuation and dry handling stability on highways.



Balanced contact pressure reduces wear and extends service life in mixed urban/off-road use.



Rim Diameter	Tire Size	Service Desc	PR	UTQG	Single Max Load (kg)	Single Max Load (lbs)	Dual Max Load (kg)	Dual Max Load (lbs)	Measuring Rim (in)	Overall Diameter (mm)	Section Width (mm)	Max Inflation Pressure (kPa)	Max Inflation Pressure (PSI)
20	265/55R20	113V	XL	600 A A	1150	2535	/	/	8 1/2J	800	277	340	49




IRON RANGER A/T KRO7

ALL-TERRAIN ADAPTABILITY

- Dedicated AT Compound
- Wide Tread Design
- Stone Ejector Design
- Reinforced Shoulder for Lateral
- Reinforced Sidewall Protection




All-terrain tread pattern design, suitable for both daily commuting and off-road driving.



Dedicated AT compound formula to meet the rubber strength and toughness requirements under various road conditions.



Wider contact surface, providing stronger grip and more stable handling.



Stone ejectors in the groove bottom, effectively reducing stone retention in the tread.



Prominent shoulder protection, delivering superior lateral grip on unpaved surfaces.



Strong and thick sidewall design, resistant to impact and tearing.



IRON RANGER A/T KRO7



Rim Diameter	Tire Size	Service Desc	PR	UTQG	Single Max Load (kg)	Single Max Load (lbs)	Dual Max Load (kg)	Dual Max Load (lbs)	Measuring Rim (in)	Overall Diameter (mm)	Section Width (mm)	Max Inflation Pressure (kPa)	Max Inflation Pressure (PSI)
14	175/75R14	86T	/	600 A B	530	1170	/	/	5J	618	177	300	44
	175/80R14	92T	XL	600 A B	630	1390	/	/	5J	636	177	340	49
	185/70R14	88T	/	600 A B	560	1230	/	/	5 1/2J	616	189	300	44
	LT175/70R14	98/96S	10PR	/	750	1655	710	1565	5J	602	177	550	80
	LT175/75R14	99/98S	8PR	/	775	1710	750	1655	5J	618	177	475	68
	LT175/80R14	95/92S	8PR	/	690	1520	630	1390	5J	636	177	475	68
15	205/60R15	91H	/	600 A A	615	1360	/	/	6J	627	209	300	44
	205/65R15	94H	/	600 A A	670	1480	/	/	6J	647	209	300	44
	205/70R15	96T	/	600 A B	710	1570	/	/	6J	669	209	300	44
	195R15C	106/104Q	8PR	/	950	2095	900	1985	5 1/2J	690	198	450	65
	LT215/75R15	100/97R	6PR	/	800	1765	730	1610	6J	703	216	350	50
	P235/75R15	105T	/	600 A B	925	2039	/	/	6 1/2J	733	235	300	44
	LT235/75R15	116/113S	10PR	/	1250	2755	1150	2535	6 1/2J	733	235	550	80
	31X10.50R15LT	109S	6PR	/	1030	2270	/	/	8 1/2J	775	268	350	50
	LT205/60R15	98/95S	8PR	/	750	1655	690	1520	6J	627	209	475	68
	LT205/65R15	99/96S	8PR	/	775	1710	710	1565	6J	647	209	450	65
	LT205/70R15	96/93S	6PR	/	710	1565	650	1435	6J	669	209	350	50
16	LT235/70R16	110/107S	8PR	/	1060	2335	975	2150	7J	736	240	450	65
	P245/70R16	111T	XL	600 A B	1090	2403	/	/	7J	750	248	340	49
	LT245/70R16	118/115S	10PR	/	1320	2910	1215	2680	7J	750	248	550	80
	LT255/70R16	115/112S	8PR	/	1215	2680	1120	2470	7 1/2J	764	260	450	65
	P265/70R16	111T	/	600 A B	1090	2403	/	/	8J	778	272	300	44
	LT265/70R16	121/118S	10PR	/	1450	3195	1320	2910	8J	778	272	550	80
	LT245/75R16	120/116R	10PR	/	1380	3042	1260	2778	7J	774	248	550	80
	LT265/75R16	123/120S	10PR	/	1550	3415	1400	3085	7 1/2J	804	267	550	80
	LT285/75R16	126/123R	10PR	/	1700	3750	1550	3415	8J	834	286	550	80
17	215/60R17	100T	XL	600 A A	800	1764	/	/	6 1/2J	690	221	340	49
	225/60R17	103H	XL	600 A A	875	1929	/	/	6 1/2J	702	228	340	49
	225/65R17	102T	/	600 A A	850	1874	/	/	6 1/2J	724	228	300	44
	235/65R17	108H	XL	600 A A	1000	2205	/	/	7J	738	240	340	49
	LT245/65R17	111/108S	8PR	/	1090	2405	1000	2205	7J	750	248	450	65
	LT245/70R17	119/116S	10PR	/	1360	3000	1250	2755	7J	776	248	550	80
	P265/70R17	115T	/	600 A B	1215	2679	/	/	8J	804	272	300	44
	P265/65R17	112S	/	600 A A	1120	2469	/	/	8J	776	272	300	44
	LT265/65R17	120/117S	10PR	/	1400	3085	1285	2835	8J	776	272	550	80
	LT265/70R17	123/120R	10PR	/	1550	3415	1400	3085	8J	804	272	550	80
	LT285/70R17	126/123S	10PR	/	1700	3750	1550	3415	8 1/2J	832	292	550	80
	LT215/60R17	109/107S	8PR	/	1030	2270	975	2150	6 1/2J	690	221	475	68
	LT225/60R17	104/101S	8PR	/	900	1985	825	1820	6 1/2J	702	228	450	65
18	235/60R18	103T	/	600 A A	875	1929	/	/	7J	739	240	300	44
	LT265/60R18	119/116S	10PR	/	1360	3000	1250	2755	8J	775	272	550	80
	LT265/65R18	122/119S	10PR	/	1500	3305	1360	3000	8J	801	272	550	80
	LT275/70R18	125/122S	10PR	/	1650	3640	1500	3305	8J	843	279	550	80
	LT285/60R18	122/119S	10PR	/	1500	3305	1360	3000	8 1/2J	799	292	550	80
	LT235/60R18	108/104S	8PR	/	1000	2205	900	1985	7J	739	240	450	65
19	LT265/55R19	119/116S	10PR	/	1360	3000	1250	2755	8 1/2J	775	277	550	80
	LT245/55R19	110/107S	8PR	/	1060	2335	975	2150	7 1/2J	753	253	450	65
20	LT265/50R20	115/112S	10PR	/	1215	2680	1120	2470	8 1/2J	774	277	550	80
	LT285/50R20	119/116S	10PR	/	1360	3000	1250	2755	9J	794	297	550	80

GREATRIP K603

HIGH WEAR RESISTANCE & LONG MILEAGE

- Low Noise & Comfortable Commuting
- Balanced Wet/Dry Traction & Safety
- Low Rolling Resistance & Fuel Efficiency



Rim Diameter	Tire Size	Service Desc	PR	UTQG	Single Max Load (kg)	Single Max Load (lbs)	Dual Max Load (kg)	Dual Max Load (lbs)	Measuring Rim (in)	Overall Diameter (mm)	Section Width (mm)	Max Inflation Pressure (kPa)	Max Inflation Pressure (PSI)
14	175/70R14C	95/93S	6PR	/	690	1520	650	1435	5J	177	602	375	54
	175/65R14C	90/88T	6PR	/	600	1325	560	1235	5J	177	584	375	54

GREATRIP K605

ULTRA-LOW NOISE PERFORMANCE

- Superior Ride Comfort
- Enhanced Wear Resistance & Long Mileage
- Reliable Dry & Wet Traction
- Precise Steering Response
- Low Rolling Resistance & Fuel Efficiency




Rim Diameter	Tire Size	Service Desc	PR	UTQG	Single Max Load (kg)	Single Max Load (lbs)	Dual Max Load (kg)	Dual Max Load (lbs)	Measuring Rim (in)	Overall Diameter (mm)	Section Width (mm)	Max Inflation Pressure (kPa)	Max Inflation Pressure (PSI)
14	185/60R14	82H	/	400 A A	475	1050	/	/	5 1/2J	189	578	300	44
	185/65R14C	95/93T	6PR	/	690	1520	650	1435	5 1/2J	189	596	375	54
	185/70R14C	96/93S	8PR	/	710	1565	650	1435	5 1/2J	189	616	450	65
15	185/60R15	84H	/	400 A A	500	1100	/	/	5 1/2J	189	603	300	44
	185/65R15	88H	/	400 A A	560	1230	/	/	5 1/2J	189	621	300	44
	195/55R15	85V	/	400 A A	515	1140	/	/	6J	201	595	300	44
	195/60R15	88V	/	400 A A	560	1230	/	/	6J	201	615	300	44
	195/65R15	91V	/	400 A A	615	1360	/	/	6J	201	635	300	44
	205/60R15	91V	/	400 A A	615	1360	/	/	6J	209	627	300	44
	205/65R15	94V	/	400 A A	670	1480	/	/	6J	209	647	300	44
	205/55R16	91V	/	400 A A	615	1360	/	/	6 1/2J	214	632	300	44




GREATRIP KG06

EXCEPTIONAL HANDLING PERFORMANCE


- Excellent wetland slip resistance performance
- Silent and comfortable driving experience
- Low rolling resistance for energy and fuel efficiency, compatible with new energy vehicle models
- Uniform wear resistance and long service life
- High-speed straight-line stability performance



Ultra-high handling performance. Asymmetric rigid pattern blocks provide strong lateral support, ensuring sensitive steering, stable cornering and outstanding control experience.




Excellent wet-skid resistance. Wide main grooves and lateral sipes drain water rapidly to avoid hydroplaning, realizing reliable grip and braking safety on wet roads.



Quiet and comfortable ride. Variable pitch noise reduction structure reduces rolling noise and vibration, creating a quiet and comfortable cockpit environment.



Uniform wear & long service life. Even contact pressure and wear-resistant compound prevent abnormal wear and extend tire life.



High-speed straight-line stability. Reinforced central rib improves tread rigidity for stable and drift-free driving at high speed.

GREATRIP KG06



Rim Diameter	Tire Size	Service Desc	PR	UTQG	Single Max Load (kg)	Single Max Load (lbs)	Dual Max Load (kg)	Dual Max Load (lbs)	Measuring Rim (in)	Overall Diameter (mm)	Section Width (mm)	Max Inflation Pressure (kPa)	Max Inflation Pressure (PSI)
16	195/55R16	91V	XL	520 A A	615	1360	/	/	6J	201	620	340	49
17	205/40ZR17	84W	XL	520 A A	500	1100	/	/	7 1/2J	212	596	340	49
	205/45ZR17	88W	XL	520 A A	560	1230	/	/	7J	206	616	340	49
	205/50ZR17	93W	XL	520 A A	650	1430	/	/	6 1/2J	214	638	340	49
	225/45ZR17	94W	XL	520 A A	670	1480	/	/	7 1/2J	225	634	340	49

Better Balanced Tires

Powered by ZERO WAVE™ Technology

KOYOYAMA TIRES



**GREATIP
K603**

**GREATIP
K606**

**GRANDTRACK
AT30**

**IRON RANGER
A/T KR07**

**GRANDTRACK
AT25**

**GREATIP
K605**

KOYOYAMA
TIRES

Shandong Zhongyi Rubber Co., Ltd

Add: Dawang Economic Park, Guangrao County, Dongying City, 257335 Shandong Province, China

Web: www.koyoyamatires.com

E-mail: info@koyoyamatires.com

Mob: +86 156 6682 9250

Tel: +86 53289803880